POLYPROPYLENE CAM & GROOVE TYPE E ADAPTER X HOSE SHANK



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 08:08 PM

SKU
: 17397

BRAND
: DIXON VALVE

MODEL
: PPE50

Construction:
Manufactured from glass-filled polypropylene

How it works:
To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.
Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.

Note:
1/2" couplers and adapters will interchange with 3/4" couplers and adapters. Only the threads and barbs are 1/2".

Safety notes:
Under no circumstances should cam and groove couplings be used for compressed air or steam service!
Pressure rating is based on the seal of the mating part
Pressure rating recommendations are based on the use of mating Dixon® fittings at ambient temperature 70°F (21°C) with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon®.
Polypropylene cam and groove should not be mixed with metal fittings.
NOT recommended for use with PTFE gaskets
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Material	Polypropylene
Maximum Operating Pressure	125 PSI
Factory Part Number	PPE50
Size	3/4" x 1/2"
Weight Lb	0.0500

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us