DQC E-SERIES STRAIGHT THROUGH INTERCHANGE FEMALE PLUG- RETAIL PACKAGE

DATE
: 11/23/2026 08:11 PM

SKU
: 17698

BRAND
: DIXON VALVE

MODEL
: PW-E3F3



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Features:
Straight-Through Pressure-Wash Interchange
Interchanges with Parker ST-Series, Foster FST-Series, Tomco Series-ST, Hansen ST-Series
These plugs have no internal valves, providing maximum flow with minimum pressure drop.

Construction:
Machined components are manufactured using solid steel
Steel componentry is plated using ROHS Compliant Trivalent Chrome
Steel nipples are hardened to provide heavy duty performance.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov
Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	3/8"
Burst Pressure	14,000 PSI (966 Bar)
Description	3/8" straight thru nipples (Case Qty 20 Required)
Female Thread	NPTF
Female Thread Size	3/8"-18
Hex	7/8"

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Length	1.60 (40.6mm)
Mandatory Pkg/Box Qty	20
Material	Steel
Maximum OD	1.01 (25.7mm)
Maximum Operating Pressure	3,500 PSI (241 Bar)
Factory Part Number	PW-E3F3
Weight Lb	0.1000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us