WILKERSON FRL'S R26 HIGH PRESSURE STANDARD REGULATOR



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 12:10 AM

SKU
: 26562

BRAND
: DIXON VALVE

MODEL
: R26-02RH

Features:
0-250 PSI adjusting range
Self-relieving standard
Non-rising push/pull locking adjustment knob
Panel mount nut included
Excellent flow characteristics
Two 1/4" NPT gauge ports standard, can be used for additional outlet ports

Installation
Can be installed with the adjusting knob in any position

Note:
Use a GC240 gauge (not supplied)

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
SCFM ratings at 100 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	R26-02RH
Flow	112 SCFM
Includes	Without Gauge
Maximum Operating Pressure	300 PSIG (20.7 Bar)
Size	1/4"
Temperature Range	32°F to 150°F (0°C to 65.5°C)
Weight Lb	2.6900

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us