# WILKERSON FRL'S R26 STANDARD REGULATOR




DATE
: 11/23/2026 10:49 PM

SKU
: 26563

BRAND
: DIXON VALVE

MODEL
: R26-03R

Use:
To increase regulated pressure, pull adjusting knob up and turn clockwise.
To reduce pressure, turn knob counter clockwise.

Features:
0-125 PSI adjusting range
Non-rising push/pull locking adjustment knob
Panel mount nut standard
Excellent flow characteristics
Two 1/4" NPT gauge ports standard, can be used for additional outlet ports

Installation
Can be installed with the adjusting knob in any position

Note:
Use a GC230 gauge (not supplied)

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Factory Part Number** | R26-03R |
| **Flow** | 148 SCFM |
| **Includes** | Without Gauge |
| **Maximum Operating Pressure** | 300 PSIG (20.7 Bar) |
| **Port** | 3/8" |
| **Temperature Range** | 32°F to 150°F (0°C to 65.5°C) |
| **Weight Lb** | 2.5800 |



KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us