WILKERSON FRL'S R28 STANDARD REGULATOR



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 09:20 PM

SKU
: 26575

BRAND
: DIXON VALVE

MODEL
: R28-06R

Use:
To increase regulated pressure, pull adjusting knob up and turn clockwise.
To reduce pressure, turn knob counter clockwise.

Features:
0-125 PSI adjusting range
Self-relieving standard
Four adjusting pressure ranges available
Two 1/4" NPT gauge ports located on the front and rear faces of the body. These ports may be used as additional regulated ports or for pressure gauges.

Note:
Use a GC230 gauge (not supplied)

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	R28-06R
Flow	233 SCFM
Includes	Without Gauge
Maximum Operating Pressure	300 PSIG (20.7 Bar)
Port	3/4"
Temperature Range	32°F to 150°F (0°C to 65.5°C)
Weight Lb	2.1400

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us