WILKERSON FRL'S R30 HIGH PRESSURE HIGH FLOW REGULATOR



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:40 PM

SKU
: 26579

BRAND
: DIXON VALVE

MODEL
: R30-06RH

Use:
To increase regulated pressure, pull adjusting knob up and turn clockwise.
To reduce pressure, turn knob counter clockwise.

Features:
0-180 PSI adjusting range
Self-relieving standard
Piston operated
Two 1/4" NPT gauge ports standard, can be used for additional outlet ports

Installation
Can be installed with the adjusting knob in any position

Note:
Use a GC240 gauge (not supplied)

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
SCFM ratings at 100 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	R30-06RH
Flow	480 SCFM
Includes	Without Gauge
Maximum Operating Pressure	300 PSIG (20.7 Bar)
Size	3/4"
Temperature Range	32°F to 150°F (0°C to 65.5°C)
Weight Lb	6.0000

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us