GROOVED RIGID COUPLING-SERIES R, STYLE 5



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 08:18 PM

SKU
: 17815

BRAND
: DIXON VALVE

MODEL
: R73

Applications:
Ideal for fire protection, plumbing, low pressure air and drainage.

Specifications:
Underwriters Listed
Factory Mutual approved
Bolts: 2
Bolt Size: 1/2"
Bolt Length: 2-3/4"

Features:
Lightweight and low pressure
Small gripping teeth hold the housing into the groove allowing a straight run of pipe and preventing any flex at the joint.

Construction:
Galvanized ductile iron body

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	R73
Material	Ductile Iron
Max. End Load Lbs.	9620
Maximum Operating Pressure	175 PSI at 70°F (21°C)
Nominal Size	3"
Pipe OD	3.50"
Seal	EPDM
Weight Lb	2.7000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us