BOSS® GROUND JOINT COMPLETE FEMALE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 09:17 PM

SKU
: 25362

BRAND
: DIXON VALVE

MODEL
: RGF81

Applications:
Boss couplings are all-purpose hose couplings, universally recommended for steam hose connections. They are also widely used for air, water, fluid petroleum, chemicals and liquid petroleum gas up to 1" ID.
Boss couplings can be applied to many types of rubber, synthetic, plastic, metallic or semi-metallic hose. Consult Dixon for specific media capabilities.

Use:
Boss couplings supply a convenient threaded fitting to connect two lengths of hose, or a single length to a male or female threaded outlet.
Use with Boss Clamps.

Specifications:
Recommended for steam service up to 450°F (232°C).

Features:
The spud part of the coupling serves as one half of the connection and is usually fixed to the equipment. The stem part that is clamped to the hose is the other half. The two halves are connected or disconnected by rotating the wing nut on the spud. When connected they achieve both a mechanical, and a pressure seal.
Positive metal-to-polymer seal
Leakproof seal forms when the metal head of the stem makes contact with the patented polymer seat in the spud
The non-metallic polymer seat resists most chemicals found in manufacturing facilities, reference the Corrosion Resistance Chart for additional information.
Easy to seal

Safety notes:
Not to be used with #250, #275 or #306 Boss clamps
Worn-out hose couplings can be dangerous. They should be checked

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

regularly and replace when necessary. Each coupling user should review applications and add safety devices where indicated.

Note. Pressurized steam is an extremely dangerous commodity. Only hose, fittings, clamps and accessory items that have been approved for steam service should ever be used! Never use an unapproved item for steam service. Always follow the manufacturer's product recommendations for pressurized steam handling.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	RGF81
Mandatory Pkg/Box Qty	1
Material	316 Stainless Steel
Seal	Positive Metal-to-Polymer Seal
Size	2" (50mm)
Thread	NPT
Weight Lb	5.6700

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us