LITE® COUPLINGS- STAINLESS STEEL



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 08:45 PM

SKU
: 25368

BRAND
: DIXON VALVE

MODEL
: RL03V

Applications:
Designed for use on rigid, locked-in pipe connections

Use:
Ideal for corrosive environments
Use of suitable anti-galling thread compound is recommended

Specifications:
Certified to ANSI/NSF 61

Construction:
316 cast stainless steel body, nuts and bolts

Compatibility & Interchange Data:
Comparable to Grinnell's # 7400 SS

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	RL03V
Material	316 Stainless Steel
Max. End Load Lbs.	2886
Maximum Operating Pressure	300 PSI
Number of Bolts	2 Bolts (Size: 1/2" , Length: 2-3/4")
Pipe OD	3.500
Seal	Fluoro-elastomer Gasket

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Size	3"
Weight Lb	3.4000

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us