BOSS® MALE STEM

DATE
: 11/23/2026 07:08 PM

SKU
: 25376

BRAND
: DIXON VALVE

MODEL
: RMS6



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Applications:
Boss couplings are all-purpose hose couplings, universally recommended for steam hose connections. They are also widely used for air, water, fluid petroleum, chemicals and liquid petroleum gas up to 1" ID.
Boss couplings can be applied to many types of rubber, synthetic, plastic, metallic or semi-metallic hose. Consult Dixon for specific media capabilities.

Use:
Use with Boss Clamps

Specifications:
Recommended for steam service up to 450°F (232°C).

Note:
For safety tags and safety tape see the Maintenance & Repair section

Safety notes:
Worn-out hose couplings can be dangerous. They should be checked regularly and replace when necessary. Each coupling user should review applications and add safety devices where indicated.
Note. Pressurized steam is an extremely dangerous commodity. Only hose, fittings, clamps and accessory items that have been approved for steam service should ever be used! Never use an unapproved item for steam service. Always follow the manufacturer's product recommendations for pressurized steam handling.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	RMS6
Hose Shank Size	3/4" (20mm)
Male Thread	NPT
Male Thread Size	3/4" (20mm)
Material	316 Stainless Steel
Weight Lb	0.4300

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us