JUMP SIZE KING COMBINATION NIPPLE NPT THREADED



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 08:36 PM

SKU
: 27626

BRAND
: DIXON VALVE

MODEL
: RST3025

Applications:
Recommended for low-pressure discharge and suction service for compatible liquids
Use:
Crimp sleeves are available and recommended for reliable assemblies.
Safety notes:
The working pressure may vary with the construction of the hose, the type of clamping system used and the application. Consult Dixon for recommendations.
In accordance with the R.M.A. bulletin for oil suction and discharge hose, a coupled length of hose in any size, should be tested to 1-1/2 times the working pressure and held for fifteen minutes without leaking or coupling movement. For additional information and detailed instruction on testing procedures, see the Rubber Manufacturers Association (R.M.A.) handbook.
Not for compressible products such as air or nitrogen
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Hose Shank Size	2-1/2"
Material	316 Stainless Steel
Factory Part Number	RST3025
Thread	NPT
Thread Size	2"
Weight Lb	1.6600

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us