ALUMINUM STORZ X FEMALE SWIVEL BUTTERFLY VALVE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 02:29 AM

SKU
: 19195

BRAND
: DIXON VALVE

MODEL
: SFBTFLY5045F

Applications:
This valve permits safe controlled flow to the intake pump and can be used in draft situations.

Use:
This unit can be used in either direction i.e.: inlet/outlet.

Construction:
ASTN A-126 cast iron cast iron body with standard 10-position locking style lever
Body wafer is lightweight aluminum cast 356-T6
3/4" push pull drain valve
Buna Seat
Finish hardcoat anodized cast aluminum bolt flanges- minimum thickness 0.001"

Note:
Lever handle to center valve is 10-1/4"

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Height	18.0"
Length	9.5"
Factory Part Number	SFBTFLY5045F
Pressure Rating	185 PSI
Storz Size	5"
Swivel Thread	NST (NH)
Swivel Thread Size	4-1/2"
Width	11.0"

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us