SHD-SERIES SCHRADER PNEUMATIC MALE THREADED PLUG





DATE
: 11/23/2026 09:02 PM

SKU
: 19284

BRAND
: DIXON VALVE

MODEL
: SHD2M1

Construction:
Machined components are manufactured using solid bar stock.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Compatibility & Interchange Data:
Schrader Twist-Lock Interchange
Parker Twist-Lock, Tomco Series-TL, Foster SHD

Safety notes:
It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/4"
Burst Pressure	6500 PSI (448 bar)
Factory Part Number	SHD2M1
Hex	11/16"
Length	1.54"
Material	Steel
Maximum OD	0.79"
Maximum Operating Pressure	300 PSI (20 bar)

** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	NPT
Thread Size	1/8"
Weight Lb	0.1200

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us