# SURELOCK? MALE NPT END




** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 09:33 PM

SKU
: 19447

BRAND
: DIXON VALVE

MODEL
: SL075M

Applications:
Coupling for air service only, commonly used in construction and mining; excels in services where ease, economy, safety and speed are paramount

Features:
The pressure activated gasket allows easy coupling (less than 15 lbs. of force is required to connect the coupling) and gaskets seal upon introduction of line pressure.

Construction:
Body: SG iron AS1831 400-250-12
Bellow seal: natural rubber (patent pending)
Safety pin is supplied with each coupling

Available Options:
Other seal materials are available upon request, contact Dixon.

Safety notes:
Safety pin is supplied with each coupling and is required as a safety precaution
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Factory Part Number** | SL075M |
| **Material** | Iron |
| **Seal** | Natural Rubber |
| **Size** | 3/4" |
| **Style** | Small Head |
| **Weight Lb** | 0.5200 |
| **Working Pressure** | 200 PSIG at 70°F (21°C) |



KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us