# DIXON SANITARY PRESSURE RELIEF VALVE L STYLE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 12:55 AM

SKU
: 19566

BRAND
: DIXON VALVE

MODEL
: SPR-LCV3A150

Applications:
Suitable for liquids and gas

Specifications:
3-A Certified

Features:
Valve opens when the set pressure is reached to prevent excess pressure in piping or systems
Valve body made from solid bar
Patented squeeze clamp
Low spare part cost

Construction:
Clamp End connection, others available on request
Wetted Product Surfaces: 32Ra, other surface finishes available
Product Contact: 316L Stainless Steel
Non product contact: 304 Stainless Steel
Actuation: Manual

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Material** | 316 Stainless Steel |
| **Maximum Temperature** | 266°F (130°C) |
| **Order Note** | Valves can be preset at the factory, advise set pressure at time of order if known. |
| **Factory Part Number** | SPR-LCV3A150 |
| **Pressure Range** | 100-300 PSI |
| **Seat** | FKM |
| **Size** | 1-1/2" |
| **Style** | L-Body |
| **Temperature Rating** | Sterilization: 300°F (148°C) maximum 20 min |
| **Weight Lb** | 6.2000 |



KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us