DIXON SANITARY PRESSURE RELIEF VALVE T STYLE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 12:22 AM

SKU
: 19577

BRAND
: DIXON VALVE

MODEL
: SPR-TCV2A200

Applications:
Suitable for liquids and gas

Specifications:
3-A Certified

Features:
Valve opens when the set pressure is reached to prevent excess pressure in piping or systems
Valve body made from solid bar
Patented squeeze clamp
Low spare part cost

Construction:
Clamp End connection, others available on request
Wetted Product Surfaces: 32Ra, other surface finishes available
Product Contact: 316L Stainless Steel
Non product contact: 304 Stainless Steel
Actuation: Manual

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Material	316 Stainless Steel
Maximum Temperature	266°F (130°C)
Order Note	Valves can be preset at the factory, advise set pressure at time of order if known.
Factory Part Number	SPR-TCV2A200
Pressure Range	50-100 PSI
Seat	FKM
Size	2"
Style	T-Body
Temperature Rating	Sterilization: 300°F (148°C) maximum 20 min
Weight Lb	8.1000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us