STAINLESS STEEL BALL VALVE FULL PORT, LOCKING HANDLE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:44 PM

SKU
: 19726

BRAND
: DIXON VALVE

MODEL
: SSLBV25

Applications:
For use in water, oil and gas applications

Features:
Blow-out proof stem
Full port
Lockable

Construction:
316 stainless steel body, ball and stem
R-PTFE seat, joint gasket and thrust washer
Plastic cover on handle

Safety notes:
Not recommended as a throttling valve
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Saturated Steam Pressure	100 PSI
Temperature Range	-20°F to 356°F (-29°C to 180°C)
Thread	female NPT x female NPT
Factory Part Number	SSLBV25
Material	316 Stainless Steel
Pressure Rating	1000 PSI WOG
Seat	R-PTFE
Size	1/4"

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Weight Lb	0.4400

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us