# DQC ST-SERIES SNAP-TITE 71 INTERCHANGE OLD STYLE FEMALE PLUG





DATE
: 11/24/2026 01:11 AM

SKU
: 19753

BRAND
: DIXON VALVE

MODEL
: ST16OF12

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Steel nipples are hardened to provide heavy duty performance.
Incorporates PTFE anti-extrusion rings to protect seal components from dynamic impulse damage.

Available Options:
Contact Dixon for all available option adders
Oxy-clean treatment is available

Compatibility & Interchange Data:
Interchangeable with Snap-Tite 71-Series

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Body Size** | 2" |
| **Burst Pressure** | 16000 PSI (1100 Bar) |
| **Factory Part Number** | ST16OF12 |
| **Hex** | 3-1/4" |
| **Length** | 4.50" (114.3mm) |
| **Material** | Steel |
| **Maximum OD** | 3.48" (88.4mm) |



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Maximum Operating Pressure** | 5000 PSI (345 bar) |
| **Temperature Range** | -40°F to +250°F (-40°C to +121°C) |
| **Thread** | Female ORB |
| **Thread Size** | 1-7/8"-12 |
| **Weight Lb** | 4.2100 |



KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us