
DQC ST-SERIES SNAP-TITE 71 INTERCHANGE FEMALE PLUG





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 09:57 PM

SKU
: 19779

BRAND
: DIXON VALVE

MODEL
: ST3F4

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Steel nipples are hardened to provide heavy duty performance.
Incorporates PTFE anti-extrusion rings to protect seal components from dynamic impulse damage.

Available Options:
Contact Dixon for all available option adders
Oxy-clean treatment is available

Compatibility & Interchange Data:
Interchangeable with Snap-Tite 71-Series

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	3/8"
Burst Pressure	27300 PSI (1800 bar)
Factory Part Number	ST3F4
Hex	1"
Length	2.32" (58.9mm)
Material	Steel
Maximum OD	1.48" (37.6mm)

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Maximum Operating Pressure	10000 PSI (700 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female NPTF
Thread Size	1/2"-14
Weight Lb	0.3600

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us