
DQC ST-SERIES SNAP-TITE 71 INTERCHANGE FEMALE PLUG





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:21 PM

SKU
: 19796

BRAND
: DIXON VALVE

MODEL
: ST6BF6-SS

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Steel nipples are hardened to provide heavy duty performance.
Incorporates PTFE anti-extrusion rings to protect seal components from dynamic impulse damage.

Available Options:
Contact Dixon for all available option adders
Oxy-clean treatment is available

Compatibility & Interchange Data:
Interchangeable with Snap-Tite 71-Series

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	3/4"
Burst Pressure	22800 PSI (1550 bar)
Factory Part Number	ST6BF6-SS
Hex	1-3/4"
Length	2.96" (75.2mm)
Material	316 Stainless Steel
Maximum OD	1.92" (48.8mm)

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Maximum Operating Pressure	5000 PSI (345 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female BSPP
Thread Size	3/4"-14
Weight Lb	1.1400

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us