HEAVY DUTY MALE X FEMALE NPT HOSE SWIVEL



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 01:40 AM

SKU
: 20082

BRAND
: DIXON VALVE

MODEL
: SWMF200

Use:
Manufactured to connect to NPT threaded hose and nozzle connections

Features:
Heavy duty internal thrust bearing and anti-friction seal design ensures swiveling at-40°F
Can be lubricated without disassembly by using the optional grease fitting kit

Construction:
Bayloy body
Hardened carbon steel swivel ball race
Through hardened chrome steel ball bearings
Buna and PTFE seals

Note:
All fuel contains additives, which can vary by fuel brand and season. Please contact Dixon with a list of all additives and we will advise of any known compatibility issues.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Material	Bayloy
Maximum Operating Pressure	150 PSI
Factory Part Number	SWMF200
Seal	Buna / PTFE
Size	2"
Thread	Male NPT x Female NPT
Weight Lb	2.9000

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us