15K THREADED NIPPLE

DATE
: 11/23/2026 05:20 PM

SKU
: 21047

BRAND
: DIXON VALVE

MODEL
: TD4F4-SS





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Construction:
Machined components are manufactured using 316 stainless steel bar stock
Stainless steel retaining ring to maximize corrosion resistance and extend service life
Seal Components: Nitrile (Buna-N) seals are standard, providing a temperature range of-40°F to 250°F (-40°C to 121°C)
Couplers have a nitrile anti-extrusion ring, providing resistance to o-ring dynamic impulse pressure damage

Compatibility & Interchange Data:
Jet Stream Screw Type
Spir Star CQD Series, DNP CRS Series

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	½?
Factory Part Number	TD4F4-SS
Hex	1-5/8?
Length	2.06?
Material	316 Stainless Steel
Maximum OD	1.75?
Maximum Operating Pressure	15,000 PSI
Temperature Range	-40°F to 250°F (-40°C to 121°C)
Thread	Female NPTF

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Thread Size	½? -14
Weight Lb	0.7100

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us