STAINLESS STEEL AIR & VACUUM RELIEF TANK VENT VALVE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 02:12 AM

SKU
: 21414

BRAND
: DIXON VALVE

MODEL
: TVSEC-G200

Applications:
Used to relieve pressure or vacuum when product filling or evacuation in a tank

Specifications:
Vacuum Break: 2" water column, 0.1 PSI
Pressure Relief: 22" water column, 0.8 PSI

Features:
Triple action valve relieves pressure as the fluid level rises while filling a tank, relieves vacuum as the fluid level drops while emptying a tank and seals under equal pressure
Stainless steel screen surrounds the entire vacuum and pressure flow area
Clamp connection standard
1/4" FNPT connection for gas inlet, plug also supplied
Repair kits available

Construction:
304 Stainless Steel
EPDM elastomer

Available Options:
Other sanitary connections optional, contact Dixon™ for information

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Elastomer	EPDM
Flow	250 GPM
Material	304 Stainless Steel
Factory Part Number	TVSEC-G200
Pressure Rating	3 PSI @ 70°F (20°C)
Tube OD	2"
Weight Lb	2.6000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us