TECTITE? BY APOLLO® PUSH TO CONNECT STRAIGHT FEMALE CONNECTOR



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 10:32 PM

SKU
: 21431

BRAND
: DIXON VALVE

MODEL
: U094

Use:
Connects copper, CPVC, PEX, PE-RT pipe in any combination

Specifications:
Certified and listed to ASSE1061, ANSI/NSF 61, and ANSI/NSF 14
Listed by IAPMO
Meets UPC, IPC and cUPC requirements

Features:
No soldering, clamps, unions or glue needed
Integral tube liner required for PEX and PE-RT installations
Easy to disconnect if needed
Can be rotated after assembly for easier installation in tight spaces

Construction:
All Tectite™ by Apollo® fittings are lead free

Compatibility & Interchange Data:
Comparable to Sharkbite®

Safety notes:
For water, dry, clean air or 100% glycol solutions only, vacuum
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	U094
Female Thread	NPT
Female Thread Size	1"
Material	Forged Brass
Maximum Operating Pressure	200 PSI
Temperature Range	32°F - 250°F (0°C - 121°C)
Thread	NPT
Tube Size	1"
Weight Lb	0.3300

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us