# DQC V-SERIES SNAP-TITE H/IH INTERCHANGE VALVED MALE PLUG





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 12:55 AM

SKU
: 21479

BRAND
: DIXON VALVE

MODEL
: V10M10-SS

Features:
General purpose hydraulic quick-connect provides superior flow characteristics with built-in reliability

Construction:
Machined components are manufactured using solid bar stock

Available Options:
Contact Dixon for all available option adders
Standard seal options include: FKM, EPDM, Steam-EP, FDA FKM, Mil-Nitrile, Fuel Nitrile and Silicone
Kalrez® seal options include: 4079, 6375 and 7075
Valve options include: Unvalved, tubular, steel, brass and 316 stainless steel
Sleeve options include: Sleeve-lock, Flanged and Silicone-flanged
Oxy-clean treatment is available

Compatibility & Interchange Data:
Interchangeable to MIL-C-51234
Snap-Tite H and Faster TNV

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Body Size** | 1-1/4" |
| **Burst Pressure** | 3000 PSI (200 bar) |
| **Factory Part Number** | V10M10-SS |
| **Hex** | 2" |
| **Length** | 3.46" (87.9mm) |
| **Material** | 316 Stainless Steel |
| **Maximum OD** | 2.19" (55.6mm) |
| **Maximum Operating Pressure** | 1500 PSI (100 bar) |
| **Temperature Range** | -40°F to +250°F (-40°C to +121°C) |
| **Thread** | Male NPTF |
| **Thread Size** | 1-1/4" - 11-1/2 |
| **Weight Lb** | 1.3500 |



KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us