DQC V-SERIES SNAP-TITE H/IH INTERCHANGE VALVED FEMALE PLUG





DATE
: 11/23/2026 11:55 PM

SKU
: 21551

BRAND
: DIXON VALVE

MODEL
: V3F3-B

Features:
General purpose hydraulic quick-connect provides superior flow characteristics with built-in reliability

Construction:
Machined components are manufactured using solid bar stock

Available Options:
Contact Dixon for all available option adders
Standard seal options include: FKM, EPDM, Steam-EP, FDA FKM, Mil-Nitrile, Fuel Nitrile and Silicone
Kalrez® seal options include: 4079, 6375 and 7075
Valve options include: Unvalved, tubular, steel, brass and 316 stainless steel
Sleeve options include: Sleeve-lock, Flanged and Silicone-flanged
Oxy-clean treatment is available

Compatibility & Interchange Data:
Interchangeable to MIL-C-51234
Snap-Tite H and Faster TNV

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Body Size	3/8"
Burst Pressure	5300 PSI (350 bar)
Factory Part Number	V3F3-B
Hex	1"
Length	1.87" (47.5mm)
Material	Brass
Maximum OD	1.10" (27.9mm)
Maximum Operating Pressure	2250 PSI (150 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female NPTF
Thread Size	3/8"-18
Weight Lb	0.2380

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us