
WS-SERIES HIGH PRESSURE WINGSTYLE CODE 62 FLANGE HEAD PLUG





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 07:12 PM

SKU
: 25687

BRAND
: DIXON VALVE

MODEL
: WS6FH6

Applications:
Used extensively in oil field and off shore oil rig applications

Features:
Interchanges with Snap-Tite 75 series
Contact Dixon ® for pressure ratings and other technical information

Construction:
Machined components are manufactured using solid steel bar stock.
Stainless steel retaining rings and springs maximize corrosion resistance and extend service life.
Steel componentry is plated using ROHS Compliant Zinc Nickel for superior corrosion resistance.
Nitrile (Buna-N) seals are standard, providing a temperature range of-40°F to +250°F (-40°C to +121°C)
PTFE anti-extrusion ring protects main coupling O-Ring from dynamic impulse pressure damage.
Main valve seal is 'housed' to improve seal integrity during pressurized connection/disconnection.

Compatibility & Interchange Data:
Snap-Tite 75-Series, Hydraulics Inc. Series- 5TV, DNP VFF-HD
Stucchi VOF, Faster OGV, Eaton FD85, Holmbury LC

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Body Size	3/4"
Factory Part Number	WS6FH6
Material	Steel
Port	3/4"
Weight Lb	1.8000

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us