WAVESEAL CLAMP



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 07:37 PM

SKU
: 21958

BRAND
: DIXON VALVE

MODEL
: WSS60

Applications:
Provides optimal retention in applications involving thermal cycling and / or high vibration.

Features:
Produces a sealing O-ring effect that prevents leakage

Construction:
5/16" head screw
Band: 201/301 Stainless Steel
Liner & Housing: 304 Stainless Steel
Screw: 410 Stainless Steel

Installation
Suggested installation torque 50-70 inch pounds, maximum recommended torque 70 inch pounds

Note:
Clamps sold 10 per box

Safety notes:
Torque ratings correspond to the torque rating of the screw of the clamp and are not an indication of the working pressure of any assembly installed with this clamp.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	WSS60
Hose OD From	3-1/4"
Hose OD To	4-1/16"
Material	Stainless Steel
Width	9/16"
Mandatory Pkg/Box Qty	10
Weight Lb	0.0001
Torque	70 in. lbs. Maximum

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us