DOUBLE DIAPHRAGM PUMP 1" ALUMINUM, TPE/ACETAL, HUSKY 1050

DATE
: 11/24/2026 01:37 AM

SKU
: 27804

BRAND
: GRACO

MODEL
: Husky 1050 / 647666



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Pneumatic Double Diaphragm Pump (AODD) in Aluminum GRACO Husky series 1050 with membranes in TPE (Hytrel), balls in Acetal and seats in TPE (Hytrel).

The Husky 1050 Air-Operated Double Diaphragm Pump features a stall-free low pulsation air valve which provides a smooth and rapid changeover. The one-piece center section eliminates leaks and reduces maintenance on Husky pumps when compared to other diaphragm pumps.

TECHNICAL SPECIFICATIONS

Brand	GRACO
Model	Husky
Series	1050
Part Number	647666
Inlet	1" NPT
Outlet	1" NPT
Flow Rate	50 GPM
Body Material	Aluminum
Fluid	Antifreeze, Detergents, Motor Oil, Hydraulic Fluid, Cutting Oil, Water, Wastewater
Diaphragms	Hytrel (TPE)
Balls	Acetal
Seats	Hytrel (TPE)
Max Size Pumpable Solids	0.125"

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Max. Suction Lift (Dry column)	16 feet
Max. Suction Lift (Wet column)	29 feet
Air Inlet	1/2" NPT (f)
Max. Cycles per Minute	280
Maximum Operating Pressure	125 PSI
Noise Level	78dB(A)@70psi / 90dB(A)@100psi
Max. Air Consumption	67 SCFM
Max. Working Temperature	150 F°
Origin	USA

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us