INDUSTRIAL PISTON PUMP 7:1, 8 GPM, MODULAR



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 10:54 PM

SKU
: 27802

BRAND
: RAASM

MODEL
: 90C/71R-55

RAASM Industrial Pneumatic piston pump series 312, R 7:1 - 8 GPM with polyurethane seals, 10.6" x 1-1/2" suction tube modular (drums and tanks), suitable for lubricant, oil and similar products.

The RAASM s. 312 industrial air-operated double-acting pumps for long distance are ideal for distribution of low to very high viscosity oils and similar products. The double-action provides a continuous flow, particularly effective in systems equipped with multiple distribution points.

TECHNICAL SPECIFICATIONS

Brand	RAASM
Ratio	7:1
Flow Rate	8 GPM
Working Pressure	90 to 120 PSI
Fluid	Fresh Oil, lubricants and similar
Suction tube	1-1/2" x 10.6"
Tube Lenght	10.6"
Air Inlet	3/8" NPT (f)
Fluid Outlet	1/2" NPT (f)
Max. Derivable Oil Viscosity	SAE 240
Seals	Polyurethane
Average Air Consumption	64 CFM
Maximum Operating Pressure	120 PSI
Noise Level	80 dB

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Bung Adaptor	Standard
Origin	Italy

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us