

DIXON® CAM & GROOVE REDUCING COUPLER X ADAPTER (TYPE DA)

FECHA : 04/23/2024 05:15 AM
SKU : 5633
MARCA : DIXON VALVE
MODELO : 6050-DA-SS



Applications:

Designed for use with liquids, consult Dixon for specific recommendations

Specifications:

Produced to interchange with all product produced to Commercial Item Description A-A-59326D

Construction:

Buna-N gasket

Produced as a welded fabrication

Available Options:

Other gasket types are available, contact Dixon.

How it works:

To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.

Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.

Note:

In reducing couplings, the coupler is the first size in the part number.

Safety notes:

Under no circumstances should cam and groove couplings be used for compressed air or steam service!

Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



* Imágenes referenciales

** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

ESPECIFICACIONES TÉCNICAS

Adapter Size	5" (125mm)
Coupler Size	6" (150mm)
Material	316 Stainless Steel
Maximum Operating Pressure	75 PSI
Factory Part Number	6050-DA-SS
Seal	Buna-N
Weight Lb	9.8650