NYLON TUBING

FECHA
: 11/23/2026 08:20 PM



SKU
: 35

MARCA
: DIXON VALVE

MODELO
: 04093

** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

Use:
Recommended for applications requiring low density, lightweight toughness, flexibility and chemical resistance
Designed for use with push-in fittings

Features:
Packaged in plastic bags
UV stabilized

Construction:
Naturally transparent
Glossy finish

Note:
NSF61 certified for potable water

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Factory Part Number	04093
Material	Nylon
Temperature Range	-40°F to 180°F (-40°C to 82°C)
Tube ID	.093"
Tube OD	1/8"
Wall Thickness	.016
Weight Lb	0.3000

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Working Pressure	270 PSI at 75°F (24°C)

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us