# NYLON TUBING




** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 08:03 PM

SKU
: 39

MARCA
: DIXON VALVE

MODELO
: 05106

Use:
Recommended for applications requiring low density, lightweight toughness, flexibility and chemical resistance
Designed for use with push-in fittings

Features:
Packaged in plastic bags
UV stabilized

Construction:
Naturally transparent
Glossy finish

Note:
NSF61 certified for potable water

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Factory Part Number** | 05106 |
| **Material** | Nylon |
| **Temperature Range** | -40°F to 180°F (-40°C to 82°C) |
| **Tube ID** | .106" |
| **Tube OD** | 5/32" |
| **Wall Thickness** | .025 |
| **Weight Lb** | 0.3940 |



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Working Pressure** | 350 PSI at 75°F (24°C) |



KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us