# POLYURETHANE- 95 DUROMETER CLEAR TUBING




** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 11:16 PM

SKU
: 335

MARCA
: DIXON VALVE

MODELO
: 1091U62R00

Applications:
Polyurethane tubing has high flexibility and a small bend radius and thus is very good for applications where space is tight.

Construction:
Clear
95 Durometer

Note:
For applications where the tubing will be exposed, black tubing is recommended.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Factory Part Number** | 1091U62R00 |
| **Material** | Polyurethane |
| **Temperature Range** | -40°F to 165°F (-40°C to 74°C) |
| **Tube ID** | .320" |
| **Tube OD** | 1/2" |
| **Wall Thickness** | .090 |
| **Weight Lb** | 3.3500 |
| **Working Pressure** | 140 PSI at 75°F (24°C) |



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us