POLYURETHANE TUBING



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 06:41 PM

SKU
: 487

MARCA
: DIXON VALVE

MODELO
: 12250

Use:
Designed for use with push-in fittings

Features:
Excellent memory, flexibility and resistance to kinking
UV stabilized

Construction:
Naturally transparent
Glossy finish

Note:
NSF61 certified for potable water

Safety notes:
Working pressure given at 75°F
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Factory Part Number	12250
Material	Polyurethane
Temperature Range	-40°F to 165°F (-40°C to 74°C)
Tube ID	.245"
Tube OD	3/8"
Wall Thickness	.0650
Weight Lb	3.2500
Working Pressure	170 PSI at 75°F (24°C)

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us