DQC E-SERIES STRAIGHT THROUGH INTERCHANGE FEMALE COUPLER





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 08:14 PM

SKU
: 676

MARCA
: DIXON VALVE

MODELO
: 12EF12-B

Features:
Straight-Through Pressure-Wash Interchange
Interchanges with Parker ST, Foster FST, Hansen ST, and Tomco ST couplings
These couplers have no internal valves, providing maximum flow with minimum pressure drop.

Construction:
Machined components are manufactured using solid brass
Stainless steel balls, retaining rings and spring maximize corrosion resistance and extend service life.
Nitrile (Buna-N) seals are standard
Steel sleeves are standard to maximize service life, hardened to resist deformation.

Available Options:
Contact Dixon® for additional seal material options, pressure ratings and other technical information.

Safety notes:
Do Not Disconnect with pressure in line.
Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	1-1/2"
Burst Pressure	5,600 PSI (386 Bar)
Factory Part Number	12EF12-B
Female Thread	NPTF
Female Thread Size	1-1/2" - 11-1/2
Hex	2-3/4"
Length	2.90 (73.7mm)
Material	Brass
Maximum OD	3.00 (76.2mm)
Maximum Operating Pressure	1,400 PSI (97 Bar)
Seal	Buna-N
Temperature Range	-40°F - +250°F (-40°C - +121°C)
Weight Lb	2.7400

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us