# NON-COLLAPSIBLE FIRE AND UTILITY HOSE




** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 11:27 PM

SKU
: 1462

MARCA
: DIXON VALVE

MODELO
: 15B15-100RAS

Construction:
Outer construction is designed to withstand abrasion
Coupled with female and male NPSH thread, rocker lug, aluminum expansion ring couplings

Available Options:
Consult Dixon™ for pricing and availability of other lengths, threads and configurations.
Also available with chrome brass fittings

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Bowl Size** | 1-1/2" |
| **Burst Pressure** | 600 PSI at ambient temperature 70°F (21°C) |
| **Color** | Red |
| **Coupling Type** | Aluminum Expansion Ring, Rocker Lug |
| **Factory Part Number** | 15B15-100RAS |
| **Hose Size** | 1-1/2" |
| **Thread** | NPSH |
| **Weight Lb** | 65.0000 |
| **Working Pressure** | 200 PSI at ambient temperature 70°F (21°C) |



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## ESPECIFICACIONES TÉCNICAS



KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us