NON-COLLAPSIBLE FIRE AND UTILITY HOSE



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 10:11 PM

SKU
: 1466

MARCA
: DIXON VALVE

MODELO
: 15B15-50RBF

Construction:
Outer construction is designed to withstand abrasion
Coupled with female and male NST (NH) thread, rocker lug, brass expansion ring couplings

Available Options:
Consult Dixon™ for pricing and availability of other lengths, threads and configurations.
Also available with chrome brass fittings

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Bowl Size	1-1/2"
Burst Pressure	600 PSI at ambient temperature 70°F (21°C)
Color	Red
Coupling Type	Brass Expansion Ring, Rocker Lug
Factory Part Number	15B15-50RBF
Hose Size	1-1/2"
Thread	NST (NH)
Weight Lb	52.0000
Working Pressure	200 PSI at ambient temperature 70°F (21°C)

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us