
# DQC E-SERIES STRAIGHT THROUGH INTERCHANGE FEMALE COUPLER



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 08:40 PM

SKU
: 1775

MARCA
: DIXON VALVE

MODELO
: 16EF16-B

Features:
Straight-Through Pressure-Wash Interchange
Interchanges with Parker ST, Foster FST, Hansen ST, and Tomco ST couplings
These couplers have no internal valves, providing maximum flow with minimum pressure drop.

Construction:
Machined components are manufactured using solid brass
Stainless steel balls, retaining rings and spring maximize corrosion resistance and extend service life.
Nitrile (Buna-N) seals are standard
Steel sleeves are standard to maximize service life, hardened to resist deformation.

Available Options:
Contact Dixon® for additional seal material options, pressure ratings and other technical information.

Safety notes:
Do Not Disconnect with pressure in line.
Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Body Size** | 2" |
| **Burst Pressure** | 5,600 PSI (386 Bar) |
| **Factory Part Number** | 16EF16-B |
| **Female Thread** | NPTF |
| **Female Thread Size** | 2" - 11-1/2 |
| **Hex** | 3-1/2" |
| **Length** | 3.00 (76.2mm) |
| **Material** | Brass |
| **Maximum OD** | 3.83 (97.3mm) |
| **Maximum Operating Pressure** | 1,400 PSI (97 Bar) |
| **Seal** | Buna-N |
| **Temperature Range** | -40°F - +250°F (-40°C - +121°C) |
| **Weight Lb** | 4.7700 |



KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us