
PD-SERIES DIAGNOSTIC FEMALE COUPLER





FECHA
: 11/23/2026 08:12 PM

SKU
: 2063

MARCA
: DIXON VALVE

MODELO
: 1PDF1

Construction:
Machined components are manufactured using solid bar stock
Stainless steel springs. Carbon steel balls and retaining rings.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Nitrile (Buna-N) seals are standard
PTFE anti-extrusion ring protects main coupler O-ring from dynamic impulse pressure damage.

Compatibility & Interchange Data:
Interchangeable to ISO15171-1
Parker PD-Series, Aeroquip FD90

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

ESPECIFICACIONES TÉCNICAS

Body Size	1/8"
Burst Pressure	18700 PSI (1300 bar)
Factory Part Number	1PDF1
Hex	21mm
Length	2.13" (54.1mm)
Material	Steel
Maximum OD	0.98" (24.9mm)
Maximum Operating Pressure	6000 PSI (400 bar) at 70°F (21°C)
Temperature Range	-40°F - +250°F (-40°C - +121°C)
Thread	Female NPT

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Thread Size	1/8"-27
Weight Lb	0.2800

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us