
# PD-SERIES DIAGNOSTIC FEMALE COUPLER



FECHA
: 11/23/2026 08:34 PM

SKU
: 2064

MARCA
: DIXON VALVE

MODELO
: 1PDF2

Construction:
Machined components are manufactured using solid bar stock
Stainless steel springs. Carbon steel balls and retaining rings.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Nitrile (Buna-N) seals are standard
PTFE anti-extrusion ring protects main coupler O-ring from dynamic impulse pressure damage.

Compatibility & Interchange Data:
Interchangeable to ISO15171-1
Parker PD-Series, Aeroquip FD90

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Body Size** | 1/8" |
| **Burst Pressure** | 18700 PSI (1300 bar) |
| **Factory Part Number** | 1PDF2 |
| **Hex** | 21mm |
| **Length** | 2.13" (54.1mm) |
| **Material** | Steel |
| **Maximum OD** | 0.98" (24.9mm) |
| **Maximum Operating Pressure** | 6000 PSI (400 bar) at 70°F (21°C) |
| **Temperature Range** | -40°F - +250°F (-40°C - +121°C) |
| **Thread** | Female NPT |

** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Thread Size** | 1/4"-18 |
| **Weight Lb** | 0.2600 |



KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us