ONE PIECE ALUMINUM BUTTERFLY VALVE WITH IRON DISC



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 11:32 PM

SKU
: 2076

MARCA
: DIXON VALVE

MODELO
: 2-400-1500

Applications:
Butterfly valves are commonly used on dry bulk tankers to control the flow of product

Use:
Designed to be placed between 2 ASME/ANSI 125 or 150 lb. flanges.

Features:
Handles are high strength 713 aluminum, with a retrogressive re-aging process which creates as stronger handle than the cast iron handle which are commonly used in the industry.
Iron discs are standard for superior wear resistance

Construction:
Aluminum body with iron disc
Polymer bushings
FDA approved black Buna-N (Nitrile) seals and seats
Stainless steel spring, stem and locking lever pin
Aluminum handle and throttling plate

Note:
Flange gaskets are not required; the valves elastomer seat also doubles as the flange gasket.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	2-400-1500
Material	Aluminum
Seal	Black Buna
Size	2"
Used on	125/150# Flange
Weight Lb	2.5700

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us