MALE NPT X PUSH-ON HOSE BARB



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 11:37 PM

SKU
: 2768

MARCA
: DIXON VALVE

MODELO
: 2720804SS

Specifications:
Number of Barbs: 2
Barb Length: 1.02"

Construction:
Dryseal

Installation
Assembly Instructions:
1. Trim hose end with smooth square cut.
2. Lubricate either push-on fitting, hose or both.
3. Insert push-on fitting into hose until first barb is in hose.
4. Place end of fitting against a flat object (bench, wall, etc.) and grip the hose one inch from end. Push with a steady force until end of hose is covered by yellow plastic cap.

Instructions
Disassembly instructions:
1. Leaving push-on fitting in place, make a 1" cut in the hose along the barbed end of the fitting. Note: Be careful not to nick barbs when cutting the hose.
2. With firm grip on hose, give a sharp downward pull to release the fitting from the hose.

Note:
No hose clamps or ferrules are needed

Safety notes:
Dixon push-on fittings are intended for use with Lok-On (push-on style) hose only.
Caution: Push-on fittings will properly grip push-on hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

cap.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Factory Part Number	2720804SS
Component Material	Yellow Plastic Cap
Weight Lb	0.0862
Hex	11/16"
Hose ID	1/2"
Length	1.86"
Male Thread	NPT
Male Thread Size	1/4"-18
Material	303 Stainless Steel
Pressure Rating	350 PSI
Temperature Range	-40°F to 150°F

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us