FEMALE NPTF X PUSH-ON HOSE BARB



FECHA
: 11/23/2026 11:26 PM

SKU
: 2840

MARCA
: DIXON VALVE

MODELO
: 2741616C

Specifications:
Number of Barbs: 3
Barb Length: 1.50"

Construction:
Dryseal

Installation
Assembly Instructions:
1. Trim hose end with smooth square cut.
2. Lubricate either push-on fitting, hose or both.
3. Insert push-on fitting into hose until first barb is in hose.
4. Place end of fitting against a flat object (bench, wall, etc.) and grip the hose one inch from end. Push with a steady force until end of hose is covered by yellow plastic cap.

Instructions
Disassembly instructions:
1. Leaving push-on fitting in place, make a 1" cut in the hose along the barbed end of the fitting. Note: Be careful not to nick barbs when cutting the hose.
2. With firm grip on hose, give a sharp downward pull to release the fitting from the hose.

Note:
No hose clamps or ferrules are needed

Safety notes:
Dixon push-on fittings are intended for use with Lok-On (push-on style) hose only.
Lok-On fittings will properly grip Lok-On hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.

** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	2741616C
Component Material	Yellow Plastic Cap
Weight Lb	0.3750
Female Thread	NPTF
Female Thread Size	1"-11-1/2
Hex	1-7/16"
Hose ID	1"
Length	2.68"
Material	Brass
Pressure Rating	350 PSI
Temperature Range	-40°F to 150°F

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us