FEMALE 37° JIC SWIVEL X PUSH-ON HOSE BARB



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 01:03 AM

SKU
: 2924

MARCA
: DIXON VALVE

MODELO
: 2880609CBC

Specifications:
Number of Barbs: 2
Barb Length:.92"

Installation
Trim hose end with a smooth square cut.
Lubricate either Lok-On fitting, hose or both.
Insert Lok-on fitting into hose until first barb is in the hose.
Place end of fitting against a flat object (bench, wall, etc.) and grip the hose one inch from the end. Push with a steady force until the end of the hose is covered by the yellow plastic cap.

Note:
No hose clamps or ferrules are needed

Safety notes:
Dixon push-on fittings are intended for use with Lok-On (push-on style) hose only.
Lok-On fittings will properly grip Lok-On hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	2880609CBC
Component Material	Brass Cap
Weight Lb	0.0650
Female Thread	UNF
Female Thread Size	9/16"-18
Hex	11/16"
Hose ID	3/8"
Length	1.75"
Material	Brass
Pressure Rating	350 PSI
Temperature Range	-40 to +150°F
Tube OD	3/8"

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us