RIGID TUBE X PUSH-ON HOSE BARB



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 11:18 PM

SKU
: 2969

MARCA
: DIXON VALVE

MODELO
: 2940404C

Specifications:
Tube Length: 1.06"
Number of Barbs: 2
Barb Length:.77"

Installation
Assembly Instructions:
1. Trim hose end with smooth square cut.
2. Lubricate either push-on fitting, hose or both.
3. Insert push-on fitting into hose until first barb is in hose.
4. Place end of fitting against a flat object (bench, wall, etc.) and grip the hose one inch from end. Push with a steady force until end of hose is covered by yellow plastic cap.

Instructions
Disassembly instructions:
1. Leaving push-on fitting in place, make a 1" cut in the hose along the barbed end of the fitting. Note: Be careful not to nick barbs when cutting the hose.
2. With firm grip on hose, give a sharp downward pull to release the fitting from the hose.

Note:
No hose clamps or ferrules are needed

Safety notes:
Dixon push-on fittings are intended for use with Lok-On (push-on style) hose only.
Caution: Push-on fittings will properly grip push-on hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	2940404C
Component Material	Yellow Plastic Cap
Weight Lb	0.0180
Hose ID	1/4"
Length	1.88"
Material	Brass
Pressure Rating	350 PSI
Temperature Range	-40 to +150°F
Tube OD	1/4"

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us