# DQC E-SERIES STRAIGHT THROUGH INTERCHANGE FEMALE COUPLER





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 08:04 PM

SKU
: 3070

MARCA
: DIXON VALVE

MODELO
: 2EF2-S

Features:
Straight-Through Pressure-Wash Interchange
Interchanges with Parker ST, Foster FST, Hansen ST, and Tomco ST couplings
These couplers have no internal valves, providing maximum flow with minimum pressure drop.

Construction:
Machined components are manufactured using 303 stainless steel bar stock
Stainless steel balls, retaining rings and spring maximize corrosion resistance and extend service life.
Nitrile (Buna-N) seals are standard

Available Options:
Contact Dixon® for additional seal material options, pressure ratings and other technical information.

Safety notes:
Do Not Disconnect with pressure in line.
Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Body Size** | 1/4" |
| **Burst Pressure** | 26,800 PSI (1,848 Bar) |
| **Factory Part Number** | 2EF2-S |
| **Female Thread** | NPTF |
| **Female Thread Size** | 1/4"-18 |
| **Hex** | 13/16" |
| **Length** | 1.46 (37.1mm) |
| **Material** | 303 Stainless Steel |
| **Maximum OD** | 0.94 (23.8mm) |
| **Maximum Operating Pressure** | 6,700 PSI (462 Bar) |
| **Seal** | Buna-N |
| **Temperature Range** | -40°F - +250°F (-40°C - +121°C) |
| **Weight Lb** | 0.1500 |



KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us