M-SERIES ARO PNEUMATIC MANUAL MALE THREADED COUPLER





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 09:17 PM

SKU
: 22312

MARCA
: DIXON VALVE

MODELO
: 2MM2-B

Specifications:
Rated pressure for connected Brass Coupler & Brass Plug: 300 PSI (20 bar) Maximum Working and 12,700 PSI (876 bar) Burst
Rated pressure for connected Brass Coupler & Steel Plug: 300 PSI (20 bar) Maximum Working and 12,400 PSI (855 bar) Burst

Construction:
Machined components are manufactured using solid bar stock.
Stainless steel springs. Carbon steel balls and retaining rings.
Nitrile (Buna-N) seals are standard

Compatibility & Interchange Data:
ARO 210
Parker 50-Series and Amflo Type 'B'

Safety notes:
It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	1/4"
Factory Part Number	2MM2-B
Hex	3/4"
Length	2.13"
Material	Brass
Maximum OD	0.87"
Pressure Rating	See Product Details
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	NPT
Thread Size	1/4"
Weight Lb	0.1750

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us