U-SERIES UNIVERSAL PNEUMATIC STANDARD HOSE BARB COUPLER





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 09:45 PM

SKU
: 22329

MARCA
: DIXON VALVE

MODELO
: 2US3-B

Specifications:
Rated pressure when connected with Steel DF Plug: 2,800 PSI (193 bar) Burst
Rated pressure when connected with Steel CJ Plug: 9,500 PSI (655 bar) Burst
Rated pressure when connected with Steel J Plug: 6,400 PSI (441 bar) Burst
Rated pressure when connected with Steel M Plug: 4,300 PSI (297 bar) Burst

Construction:
Machined components are manufactured using solid bar stock.
Stainless steel springs. Carbon steel balls and retaining rings.
Valve components are machined from solid brass bar stock.
Nitrile (Buna-N) seals are standard

Compatibility & Interchange Data:
2U-Series 6-in-1 (ARO 210, Industrial, Truflate, Lincoln, Italian, and CEJN 320)
Parker UC-Series, Hansen Auto-Flo 23 and Coilhose Series UC

Safety notes:
Operating pressure for couplings utilizing hose barb connections may be dramatically reduced to that of the hose rating and/or hose end connection combination. Consult hose manufacturer's catalog for hose end connection ratings. If in doubt, test under controlled conditions for suitability to application. Dixon cannot assume liability for misapplication of production resulting in equipment down-time, lost production, and/or personal injury including death.
It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

Note: Many competitive Universal couplings are unable to match the performance capabilities of the Dixon U-Series. Although the universal coupler permits multiple series nipples to mate with one coupler, it is recommended to match like series couplers and nipples. When using a universal coupler, the lower performance rating between the coupler and the nipple must take precedence.

Dry Air: Some pneumatic applications require the pressurized air to be 'dried' to ensure proper operation of equipment and/or application of product (ie. Auto body shops). It is best to match like series couplers and nipples in these applications. If it is necessary to use a Universal coupler, lube the seal and valve area regularly to ensure reliable service.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Body Size	1/4"
Factory Part Number	2US3-B
Hex	3/4"
Hose ID	3/8"
Length	2.76"
Material	Brass
Maximum OD	0.92"
Maximum Operating Pressure	300 PSI (20 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Weight Lb	0.2000

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us