LEGRIS
NYLON/NICKEL-PLATED BRASS PUSH-IN MALE BRANCH TEE



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 01:35 AM

SKU
: 3650

MARCA
: DIXON VALVE

MODELO
: 31080818

Use:
Compatible tubing: semi-rigid nylon, polyurethane and polyethylene tube
Vacuum capability: vacuum of 28" Hg (99% vacuum)

Features:
Positive seal: sealing and holding is accomplished instantaneously
Reusable: connect and disconnect numerous times
Full flow: fitting seals on outside diameter of tubing
Pre-applied thread sealant on all tapered male pipe threads
The body is orientable for positioning purposes.

Construction:
Nickel-plated brass threads
Black body is glass-filled nylon
Buna-N D seal
Polypropylene release button
Silicone free

Installation
Quick connect and disconnect, no tools required.
To connect, simply push tubing in.
To disconnect, press the release ring towards the fitting and pull tubing out.

Safety notes:
Maximum circuit pressure depends equally on the type and diameter of the tube used.
Pressure rating given at ambient temperature 70°F/21°C.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	31080818
Male Thread	NPT
Male Thread Size	3/8"
Material	Nylon/Nickel-Plated Brass
Seal	Buna-N D seal
Temperature Range	-4°F to 175°F (-20°C to 79°C)
Tube OD	5/16"
Weight Lb	0.0550
Working Pressure	290 PSI at ambient temperature

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us